

# EVE P-160 RGBW

## HIGHLIGHTS

- Robust wash light designed for mobile and installation applications
- Included interchangeable magnetic lenses alter the beam to desired angles
- Full color output as well as preset white color temperatures built in.
- Built-in gel frame holder and 6¼-inch accessory slot to hold barn doors
- Fanless design ensures 100% silent operation
- Flicker-free on video due to the high-frequency LED dimming
- D-Fi USB compatibility for wireless master/slave or DMX control
- Cast aluminum housing provides extra strength without the weight
- powerCON®-compatible power input/output connections for power linking
- Fits best in the CHS-40 VIP gear bag



## SPECIFICATIONS

- DMX Channels : 4, 6 or 11
- DMX Connectors : 3- and 5-pin XLR
- Light Source : 61 LEDs (14 red, 13 green, 14 blue, 20 white) 160 W total, (3.8 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 33 Hz
- PWM Frequency : 25 kHz
- Beam Angle : 23°, 35° or 48°
- Field Angle : 50°, 63° or 85°
- Illuminance : (23°): 3,442 lux @ 2 m (no lens)  
(35°): 2,414 lux @ 2 m (lens 1)  
(48°): 1,310 lux @ 2 m (lens 2)  
(23°): 519 lux @ 5 m (no lens)  
(35°): 386 lux @ 5 m (lens 1)  
(48°): 211 lux @ 5 m (lens 2)
- Lumens : 4,880
- Power Linking : 11 units @ 120 V; 21 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 122 W, 1 A @ 120 V, 60 Hz  
121 W, 0.5 A @ 230 V, 50 Hz
- Weight : 7.8 lbs (3.6 kg)
- Size : 8.6 x 9.7 x 12 in (220 x 245 x 305 mm)
- Approvals : CE, MET, RoHS
- Accessory Holder/Gel Frame Size : 6.25 in (159 mm)
- CRI : 80 (Warm White)
- Color Temperature Range : 2700 to 6500 K
- Optional Controllers : DFI USB

## WHAT'S INCLUDED

- EVE P-160 RGBW
- Power cord
- 2 lenses
- Gel frame
- Quick Reference Guide